

## **Barracuda® GL1500 Front Fender Trim 51-260**

1. Place bike on center stand.
2. Remove front wheel covers (see Owner's Manual, Front Wheel Removal, steps 1 through 6)
3. Modify front wheel cover (see drawing).
  - a. Option 1: Measure down 1 3/8 inch from top and 5/8 inch from inside edge and drill 1/2 inch hole. Cut along Line A and either Line B or C.
  - b. Option 2: Measure down 1 5/8 inch from top (Line A) and 7/8 inch from inside edge (Line C). Cut along these lines to remove rectangular corner.
4. Remove bolt on front of fork tube that attaches fender to fork behind modification of front wheel cover. Replace bolt with provided stud inserting end with greatest amount of threads into fork tube.
5. Reinstall front wheel covers.
6. Remove 2 bolts on top of fender that attached slider protector to fender.
7. Set 1/2 inch spacers in depression where bolts were removed.
8. Put factory shouldered washer and provided 1/2 inch spacer onto stud installed in fork (step 3).
9. Put fender trim into place aligning top mount to slider protector bolt atop 1/2 inch spaces (step 7). Attach over-length bolts provided but do not tighten.
10. Seat fender trim downward and rearward onto studs over 1/2 inch spaces on studs (step 3). Put nuts on finger tight only.
11. Tighten top mount bolts.
12. Tighten nuts onto studs.

